

Microstructural effects and kinetics of high temperature oxidation in Nb-Si base alloys

**E. Sarath K Menon ,
Triplicane A. Parthasarathy
and Madan G. Mendiratta**

**UES Inc., 4404 Dayton-Xenia Road, Dayton, OH 45431
& WPAFB, Dayton, OH 45433**

Support: Air Force Contract No. F33615-01-C-5214






Report Documentation Page			Form Approved OMB No. 0704-0188					
<p>Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p>								
1. REPORT DATE 18 MAR 2004	2. REPORT TYPE N/A	3. DATES COVERED -						
4. TITLE AND SUBTITLE Microstructural effects and kinetics of high temperature oxidation in Nb-Si base alloys			5a. CONTRACT NUMBER					
			5b. GRANT NUMBER					
			5c. PROGRAM ELEMENT NUMBER					
6. AUTHOR(S)			5d. PROJECT NUMBER					
			5e. TASK NUMBER					
			5f. WORK UNIT NUMBER					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) UES Inc., 4404 Dayton-Xenia Road, Dayton, OH 45431 & WPAFB, Dayton, OH 45433			8. PERFORMING ORGANIZATION REPORT NUMBER					
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)					
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)					
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited								
13. SUPPLEMENTARY NOTES See also ADM001672., The original document contains color images.								
14. ABSTRACT								
15. SUBJECT TERMS								
16. SECURITY CLASSIFICATION OF: <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33.33%; padding: 2px;">a. REPORT NATO/unclassified</td> <td style="width: 33.33%; padding: 2px;">b. ABSTRACT unclassified</td> <td style="width: 33.33%; padding: 2px;">c. THIS PAGE unclassified</td> </tr> </table>			a. REPORT NATO/unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 25	19a. NAME OF RESPONSIBLE PERSON
a. REPORT NATO/unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified						





INTRODUCTION

- Understand the effect of alloying on microstructural modification in Nb-Ti-Si based alloys (phases formed, microstructural distribution)
- Effect of Ti, Al, Cr, C on Nb-Si alloys
(as-cast, heat-treated alloys)
- Oxidation effects on microstructures
- Future directions in the study





Phase diagrams calculated using PANDAT (Y.A. Chang et al.

Computherm, LLC)







Calculated Isothermal sections at 1200°C




$\text{Nb}_3\text{Si} \rightarrow \beta + \text{Nb}_5\text{Si}_3$ eutectoid reaction




Nb-17.2 at%Si




As cast



Nb-15.0Si-12.0Ti




$1200^\circ\text{C} - 120$ hours




Nb-15.8Ti-16.0Si

1100°C / 185 hrs




1000°C / 257 hrs




Nb-20.8Ti-15.8Si

1100°C / 185 hrs




800°C / 576 hrs



Nb-16.5Si-20Ti-xAl


1500°C 100 hours




1Al



5Al



2.5Al





Nb-16.5Si-5Al



Nb-14Si-12.5Ti

Nb-14Si-12.5Ti-2C


As cast




1500°C 100 hours




As cast microstructures




Nb-14Si-12.5Ti



Nb-14Si-12.5Ti-2C



Nb-14Si-12.5Ti-10Cr



Nb-14Si-12.5Ti-10Cr
-10Al

Equilibrium Phases and their Compositions at 1200°C




Fig. 1 (a) Nb-19.86Ti-19.74Si-4.21Ge-3.26Al-4.21Hf-9.90Cr





Fig. 1(b) Nb-25.99Ti-12.61Si-4.94Ge-1.92Al-1.90Hf-6.73Cr-0.43Sn.

1 : Nb_5Si_3 ; 2 : β solid solution phase; 3: Cr_2Nb ; Arrows : Ti_5Si_3



At. %	β		Nb_5Si_3 -type		Ti_5Si_3 -type		Cr_2Nb -type
	Fig 1(a)	Fig. 1(b)	Fig. 1(a)	Fig. 1(b)	Fig. 1(a)	Fig. 1(b)	Fig. 1(a)
Nb	53.07	57.99	38.04	38.59	28.28	26.80	21.78
Ti	30.23	26.58	18.04	22.23	26.22	29.18	12.65
Si	0.45	0.50	30.83	25.78	27.67	26.47	6.05
Ge	0.16	0.06	5.72	7.34	7.80	9.19	0.34
Hf	1.03	0.72	4.74	1.71	6.73	6.10	4.74
Al	3.35	2.60	1.19	1.54	2.13	1.22	0.98
Cr	11.72	10.06	1.43	2.41	1.17	0.90	54.81
Sn	-	1.51	-	0.41	-	0.14	-

Schematic Phase Diagram





Oxidation resistance of Nb alloys


Cyclic oxidation of pure Nb and β solid solution



Effects of alloying on cyclic oxidation






Effect of processing history on cyclic oxidation




Initial stages of oxidation

$$\Delta w = Kt^{-n}$$






1 hour





5 Hours




24 hours


Oxidation of a Nb-26Ti-13Si-5Ge-7Cr-2Al-2Hf-0.5Sn alloy at 1200°C




Effect of complex alloying




Nb-14Si-12.5Ti-10Cr



Nb₅Si₃
Nb-14Si-12.5Ti-10Cr-10Al





Nb-12.5Ti-14Si-10Mo-10Al
-5Cr-5Hf-5Zr



Nb₅Si₃
Nb-12.5Ti-14Si-20Mo-10Al
-9Cr-5Hf-5Zr


**Preferential oxidation of phases in
Nb-20Ti-20Si-4Ge-10Cr-3Al-4Hf-3B
Oxidized at 1200°C for 48 hrs**



Oxidation of Nb-30Ti-7Si-10.5Cr-9.5Al -1.1Hf-1.5Zr-0.08C



1000 °C for 24 hours




900 °C for 16 hours




2 μm

Oxidation of Nb_3Si and lamellar $\beta + \text{Nb}_5\text{Si}_3$



Nb-10.5Ti-16.5Si




Nb-20.8Ti-15.8Si




Oxidized at 1000 °C for 1 hr



Oxidized at 800 °C for 4 hrs







Nb-16.1Si-4.9Al 1 1000 °C for 1hr






Nb-20.8Ti-15.7Si-4.3Al 800 °C for 4hrs

Growth of surface oxide in Nb-26Ti-13Si-5Ge-7Cr-2Al-2Hf-0.5Sn alloy after oxidation at 800°C/ 5 hrs.



Mechanism of low temperature cracking



Conclusions

- It is possible to significantly modify the microstructural distribution of the phases in Nb alloys.
- Stability of Nb_3Si & Nb_5Si_3 is strongly influenced by alloying additions : Thermodynamic parameters associated with multicomponent systems must be modified.
- Oxidation resistance of Nb alloys can be increased by alloying.
- Oxidation behavior is affected by phase distribution in the material.
- It maybe possible to control the low temperature cracking by microstructural control.